

FEATURES


Maximum Output current I_O : 0.1 A

Output voltage V_O : 5 V

Continuous total dissipation P_D : 0.25 W ($T_a=25^\circ\text{C}$)

ABSOLUTE MAXIMUM RATINGS (Operating temperature range applies)

Parameter	Symbol	Value	Unit
Input Voltage	V_I	30	V
Operating Junction Temperature Range	T_{OPR}	-40~+125	$^\circ\text{C}$
Storage Temperature Range	T_{STG}	-65-150	$^\circ\text{C}$




ELECTRICAL CHARACTERISTICS AT SPECIFIED VIRTUAL JUNCTION TEMPERATURE ($V_i=10\text{V}$, $I_o=40\text{mA}$, $C_i=0.33\mu\text{F}$, $C_o=0.1\mu\text{F}$, unless otherwise specified)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Output voltage	V_O	$T_j=25^\circ\text{C}$	4.8	5.0	5.2	V
		$7\text{V} \leq V_i \leq 20\text{V}$, $I_o=1\text{mA} \sim 40\text{mA}$	4.75	5.0	5.25	V
		$I_o=1\text{mA} \sim 70\text{mA}$	4.75	5.0	5.25	V
Load Regulation	ΔV_O	$I_o=1\text{mA} \sim 100\text{mA}$, $T_j=25^\circ\text{C}$		15	60	mV
		$I_o=1\text{mA} \sim 40\text{mA}$, $T_j=25^\circ\text{C}$		8	30	mV
Line regulation	ΔV_O	$7\text{V} \leq V_i \leq 20\text{V}$		32	150	mV
		$8\text{V} \leq V_i \leq 20\text{V}$, $T_j=25^\circ\text{C}$		26	100	mV
Quiescent Current	I_q	$T_j=25^\circ\text{C}$		3.8	6	mA
Quiescent Current Change	ΔI_q	$8\text{V} \leq V_i \leq 20\text{V}$			1.5	mA
	ΔI_q	$1\text{mA} \leq V_i \leq 40\text{mA}$			0.1	mA
Output Noise Voltage	V_N	$10\text{Hz} \leq f \leq 100\text{KHz}$, $T_j=25^\circ\text{C}$		42		μV
Ripple Rejection	RR	$8\text{V} \leq V_i \leq 20\text{V}$, $f=120\text{Hz}$	41	49		dB
Dropout Voltage	V_d	$T_j=25^\circ\text{C}$		1.7		V

* Pulse test.

TYPICAL APPLICATION




Note: Bypass capacitors are recommended for optimum stability and transient response and should be located as close as


Possible to the regulators.

Typical Characteristics


Output Characteristics




Dropout Characteristics




Quiescent Current vs Input Voltage




Current Cut-off Grid Voltage



Output Voltage vs Junction Temperature




Power Derating Curve



Package Outline Dimensions (unit:mm)

SOT-23



Mounting Pad Layout (unit: mm)

